ROTOCUT DIE CUTTER by Ampak

MODEL: RC2400, RC3000



Specification Sheet

FEATURES

CONTROL PANEL

- Directional Switch and Emergency Stop
- Momentary Safety Operating Switch

DIE CUTTING METHOD

- Bi-Flex Cutting Principle (Cutting Force Concentrated Between 2 Pressure Rolls)
- Powered 6" Diameter Rigid Steel Pressure Rollers
- Extra Heavy Duty Self Aligning Roller Bearings
- Polypropelene Cutting Plate
- Single Point Cutting Pressure And Height Adjustment **OTHER FEATURES**
- Heavy Duty Infeed And Outfeed Rollers
- Rugged Unitized Steel Frame
- One Year Warranty

MODEL SPECS

CUTTING AREA	24", 30" (61, 76), Unlimited Length
PRODUCT HEIGHT	5" Maximum (13 cm)
ROLL CLEARANCE	1 1/4" to 5" H (3.2 to 13 cm)
BED HEIGHT	33" (84 cm)
OVERALL DIMENSIONS	43" W, 90" L, 53" H (109 W, 229 L, 135 H cm)
POWER REQUIREMENTS	115, 208, 230 Volt, Single Phase, 15 Amp
CYCLE SPEEDS	80' per minute (24.4m per minute)
WEIGHT	650 lbs. (295 kg)



AVAILABLE OPTIONS

- Rotocut RC-2400: 24"W Cutting Area
- Rotocut RC-3000: 30"W Cutting Area
- Spare Parts Kit
- Special Electrical For 220/440v, 3 Phase
- Polypropylene Cutting Plate 20" W, 26" L (51 W, 66 L cm)
- Polypropylene Cutting Plate 26" W, 32" L (66 W, 81 L cm)
- Polypropylene Cutting Plate 32" W, 38" L (81 W, 97 L cm)



Revised 2015