



World Class Printing Systems
for **Real World Applications**



CO Pilot 500

MORE OPTIONS, BETTER PRINT

Squid Ink's CoPilot 500 printing system is designed to print superior quality hi-resolution with up to 2.8" of print height per printhead and the ability to run up to 2 printheads from one controller. The CoPilot 500 offers a versatile, yet cost effective solution for your coding and marking applications.

SIMPLE TO USE CONTROL INTERFACE

CoPilot 500's 4.3" full color touchscreen provides access to the system's internal messages and print functions. Messages are created and edited on Squid Ink's easy-to-use Orion™ PC Software and transferred via USB, ethernet, wireless, or optional Windows® tablet. The tablet is ideal for users who want message creation and editing functionality on the production floor. For larger applications, an unlimited number of CoPilot 500 printing systems can be connected via ethernet or wireless network and controlled through one central Orion™ PC.

APPLICATION VERSATILITY

The system is capable of running oil-based or solvent-based inks to print up to 5.6" (2.8" from a single head) of hi-resolution characters, razor-sharp text, scannable bar codes, and great looking logos at 180 dpi. For non-porous applications, users have the option of utilizing Squid Ink's solvent-based ink to print on a variety of non-porous products like coated cartons, polystyrene, and more. Squid Ink's PZ-1000 ink for porous substrates offers ultra-low maintenance, eliminating the need for auto-priming functions and offering better ink utilization than competitive systems.

ENGINEERED FOR MAXIMUM UPTIME


The CoPilot 500 is designed to meet the harsh demands of your application. The printer features a durable touchscreen, industrial strength printhead construction, and simple ink delivery system for industrial applications. You can be confident that CoPilot 500's rugged design will withstand the most abusive industrial environments while providing superior quality print. The CoPilot 500 also features a large 500ml cartridge. The generous ink volume allows users to keep their line running, reducing downtime and maximizing ROI.

INK JET CODING AT THE RIGHT PRICE

The CoPilot 500 lets users meet the GS1 barcode specification for less. CoPilot 500 consumable costs are typically 1/10 of the cost of paper labels and eliminate pre-printed cartons and SKUs of label inventory. Any way you look at it, Squid Ink's CoPilot 500 provides users with an affordable solution to meet their ink jet coding needs.

THE RIGHT SOLUTION

Rugged design. Low maintenance operation. User friendly software. Low cost of ownership. Your benefits go on and on. When it comes to industrial ink jet printing, rely on Squid Ink to provide the right solution for your coding and marking needs.



1) Run up to two printheads from a single controller, for up to 5.6" of print per system.

2) The CoPilot 500 utilizes oil-based, or solvent-based inks for printing on a wide range of porous or non-porous substrates.

3) A 4.3" full color touchscreen provides access to the systems internal messages and print functions.

4) Manage messages wirelessly using an optional Windows® tablet with Orion Software.™

SYSTEM SPECIFICATIONS:

- **Print Technology** - Piezo impulse printhead technology
- **Maximum Print Height** - 2.8" (7.1 cm) per printhead, 5.6" (14.2 cm) total
- **Vertical Print Resolution** - 180 dpi capable of printing razor-sharp graphics, small character text, and scannable bar codes
- **Horizontal Print Resolution** - 205 dpi
- **Print Speed** - CoPilot 500 (oil-based) 205 ft/min; CoPilot 500HS (oil-based) 300 ft/min; CoPilot 500 (solvent-based) 150 ft/min
- **Time & Date** - Internal real time clock with battery back-up
- **Product Sensor** - External diffuse beam photocell standard
- **Communication Interface** - One USB host and one Ethernet input
- **Touchscreen** - 4.3" (10.9 cm) full color touchscreen display
- **Ink Cartridge Volume** - 500ml cartridge
- **Low Ink Indicator** - Status alert on touchscreen, light beacon optional
- **Substrate Capabilities** - Porous or non-porous surfaces
- **Electrical Requirements** - 100 - 240 VAC, 50/60 Hz
- **Operating Environment** - 34°F - 104°F (1° - 40°C) oil-based; 62°F - 100°F (17° - 37°C) solvent-based
- **Agency Certifications** - CE, TUV, FCC

OPTIONAL ACCESSORIES

- **Encoder** - For operation with variable speed conveyors
- **Bar Code Laser Scanner** - Allows scan and print message retrieval
- **External Light Beacon** - Indicates low ink levels
- **Wireless USB Device and Router** - For wireless connectivity
- **Windows Tablet** - Pre-loaded with Orion™ software; includes mounting bracket with swivel arm, USB to ethernet cable and stylus
- **Conveyor Mounting Bracket** - Provides stable mount to conveyor or other material handling equipment
- **Floorstand** - Includes mounting brackets and legs with leveling feet; 59" (1.5m) total height
- **Starter Kit** - Includes ink, cleaner and flush solution, printhead wipes, hand cleaner and latex gloves

SOFTWARE SPECIFICATIONS

- **Time & Date** - Full time and date functionality including expiration date and Julian Dates.
- **Item Numbering** - Sixteen counters, one of which can be a daily counter and production counter
- **Shift Codes** - Four programmable shift codes with automatic rollover
- **Bar Codes** - All standard bar codes including 2D
- **Fonts** - Arial, Arial Bold, Arial International, Arial Monospaced, Courier, Tahoma Bold and Lucida resident fonts for use in variable data elements. Static elements in any Windows® font
- **Logos** - Most image files supported with Orion software
- **Printing Features** - Reverse, invert, rotate, repeat; print on/off button
- **Message Length** - Up to 180" (4.5 m)
- **Number of Messages** - 4GB storage space will store approximately 1000+ messages
- **Ink Usage** - Shown in Orion software
- **User Data Prompts** - Prompts for user input at start of print job by manual input on touchscreen
- **Bluetooth Connectivity** - For connectivity with Bluetooth keyboards
- **Wireless Connectivity** - For wireless connection between PC or tablet and printer controller
- **Database Capability** - Ethernet communication protocol for external communication
- **Languages** - English, Spanish, German, Chinese, Japanese, Korean, Russian



©2019 Squid Ink Manufacturing, Inc. Specifications subject to change. All trademarks are the property of their registered owners. Windows™ is a registered trademark of Microsoft Corporation in the United States and other countries.



7041 Boone Avenue North, Brooklyn Park, MN 55428
 (763) 795-8856 1 (800) 877-5658
 www.squidink.com info@squidink.com



ENGAGE technologies corporation