



# LD-3SB

Semi-automatic,  
uniform case sealer

### Quick Changeover

Easy height adjustment and simple self centering wheel adjustment

### Simplifies Maintenance

Self centering belts require no adjustments along with tool-less blade and roller change on tape cartridge

### Production Versatility

Easily pairs with multiple case erectors to form a mini-pack station and sealer

### Robust Design

7 gauge steel mast and 12 gauge welded steel head and structural platform provide long-lasting durability

# LD-3SB

## Semi-automatic, uniform case sealer

The LD-3SB is an operator fed, semi-automatic, uniform, industrial grade case sealer designed to top and bottom seal corrugated cases. Ideal for tall and narrow cases. This side belt sealer is available with a narrow box option of 3 1/4".

### Features and benefits

#### ■ Performance

- Operator friendly self-centering system requires no manual adjustments which reduces wear.
- Powerful 1/6 HP high efficiency motor drive system

#### ■ Versatility

- Compact footprint
- Large case range with narrow box option
- Quick changeover

#### ■ Durability

- Robust design is ideal for 24/7 operations
- 7 gauge steel mast and 12 gauge welded steel head and structural platform

#### ■ Safety

- Motors have individual and separate overload protection
- Tape cartridge features patented locking knife guard

### Optional equipment

- Infeed and exit pack table (solid or roller)
- Top squeezers
- 3 flap folder
- Available for 3" wide tape
- High mast for box heights to 34" (864 mm)
- Casters
- Mirror image
- Spare parts kit
- NEMA 4, NEMA 12
- Narrow box option of 3 1/4"

### CaseLocker™ 60 series tape cartridges

- Patented locking knife guard system allows the blade to be exposed only when the rollers are depressed
- Telescoping tape core allows for varying tape core sizes
- Patented toolless removal of blades and wipe rollers
- Processes weak corrugated
- No lubrication points
- Utilizes link bar and knife arm bearings for added strength



### LD3-SB Technical Specifications

Power	110 volts, 60 cycle, single phase
Operating Speed	Continuous belt drive; 72' per minute (21.9 m/min.)*
Case Range	Length: 4.5" - infinite Width: 4" - 20" Height: 4-1/2" - 24
Machine Dimensions	62.25" (158 cm) high 32" (81.28 cm) long 43" (109.22 cm) wide
Weight	375 lbs. (170 kg.), uncrated
Conveyor Height	24 1/4" to 29 1/4" Standard Consult factory for other heights
3-2-1 Limited Warranty	3 Year - Tape Cartridges 2 Year - Complete drive system, motor/gear reducer 1 Year - All other parts except for wear and moving parts
Closure Material	Pressure sensitive tape

\*Production rate depends on box size and operator dexterity