



STS 1509-2 Shrink Tunnel

SHRINK TECH SYSTEMS



Features:

- * PID Temperature Control
- * Variable Speed Live Roller Conveyor.
- * Teflon Mesh Rollers Covers on Conveyor
- * Heat Guards for Operator Protection
- * High Efficiency Heating Tubes.
- * Convection Air Heating System.
- * Adjustable Blower Velocity Control

Specifications:

Machine Size:	36"l x 27"w x 50"h
Package Size:	W (Max. 13") H (Max. 7")
Chamber Size	27"l x 15"w x 9"h
Max.Conveyor Speed	98 FPM
Power Requirements	220v / 1 PH / 26 AMPS



STS 1609-3 Shrink Tunnel

SHRINK TECH SYSTEMS



Features:

- * PID Temperature Control
- * Variable Speed Live Roller Conveyor.
- * Teflon Mesh Rollers on Conveyor
- * Heat Guards for Operator Protection
- * High Efficiency Heating Tubes.
- * Convection Air Heating System.

Specifications:

Machine Size:	47"l x 26"w x 51"h
Package Size:	W (Max. 14.5") H (Max. 9")
Chamber Size	39"l x 16"w x 9"h
Max.Conveyor Speed	98 FPM
Power Requirements	220v / 3 PH / 28 AMPS

www.shrinktechsystems.com

1226 AMBASSADOR BLVD. ST. LOUIS MISSOURI 63132

PHONE: 314.997.4259 FAX: 314.995.7006