

HEAVY DUTY COMBO SHRINK SYSTEM

MODEL: HDX350



FEATURES

CONTROL PANEL

- Conveniently Positioned, **RS-5 Plus** Digital Controller with Three Year Warranty on Original Machine Controller
- Meets UL 508A Standard
- Simple Operation and Precise Temperature Controls
- Cycle Counter Comes Standard with Reset
- Single Cord 220V Single Phase Power Supply

SEALING AREA

- Hot Knife Exact Seal System with Multiple Profile Options
- Large 21" W by 25" L Seal Area
- Heavy Duty Cast Aluminum Seal Head with Stainless Film Clamps
- Balanced Magnetic Hold Down for Strong, Consistent Seals
- Seal Conveyor with Smooth Product Transfer from Seal Area to Tunnel

SHRINK TUNNEL

- Non-Stick Mesh Tunnel Belt with Adjustable Riser Bar for Improved Bottom Shrink
- Efficient MaxAir Tunnel Almost Triples the Airflow and Evenly Wraps Air Around Package
- Automatic Cool Down Extends Heating Element Life



Stainless Steel HDX350

OTHER FEATURES

- Package Centering System for Even Shrink - Sealing and Tunnel Conveyor Move in Tandem Vertically. Also, Includes Tunnel Horizontal Quick Slide Adjustment.
- Two Year Warranty
- Four Individually Adjustable Perforating Wheels
- Auto Tensioning Film Cradle
- Heavy Duty Casters and Levelers

R HS Denotes RapidHS 5 Day Program Options

MODEL SPECS

FILM CAPACITY	25" Wide (64 cm)
L BAR SEALING AREA	21" W, 25" L (53 W, 64 L cm)
INSIDE TUNNEL DIMENSIONS	27" L, 20" W, 12" H (69 L, 51 W, 30.5 H cm)
TUNNEL CONVEYOR SPEED	0-20 Feet per Minute (0-6 meters per minute)
OVERALL DIMENSIONS	95" L, 35" W, 59" H (241 L, 89 W, 150 H cm)
WORKING HEIGHT	38" (97 cm)
POWER REQUIREMENTS	220 Volts, 48 Amp, Single Phase
TUNNEL WATTAGE	7,200
WEIGHT	1080 lbs. (490 kg)

AVAILABLE OPTIONS

- Fully Stainless Steel Construction
- Left Hand Reverse Flow
- Powered Conveyor Lift
- Air Actuated Sealing Head
- Added Heated Hole Punch
- Tunnel Belt Options: Stainless Steel Wire Mesh or PTFE Non-Stick Mesh Belt
- Spare Parts Kit (5820-020) **R HS**
- Powered Film Unwind with **R HS** Tensioning Roller and 10 Inch High Adjustable Inverting Head
- GTC180/16- 180 Degree Gravity Turn Around Conveyor
- GTC90/16- 90 Degree Gravity Turn Around Conveyor
- AT36- 36" Rotary Accumulator Table
- AT48- 48" Rotary Accumulator Table



HEAVY DUTY COMBO SHRINK SYSTEM

MODEL: HDX350



MACHINE FOOTPRINT

LENGTH (L)	95"
WIDTH (W)	35" Tunnel Retracted 43" Tunnel Pulled Out
HEIGHT (H)	59" Tunnel Lowers 4"

