



RP SERIES

ROLLER DIE CUTTING MACHINES



RP28-2



RP22-1

Starview Packaging Machinery, Inc.

Toll free: 1-888-278-5555 / www.starview.net

EXPERIENCE THE STARVIEW ADVANTAGE:

- A simple and economical solution to provide steel rule die cutting for skin boards, thermoformed parts, gaskets, etc.
- Simple controls for ease of operation.
- Utilizes standard low-cost steel rule cutting dies for quick and easy changeover.
- Starview exclusive soft-start and soft-stop solid state drive system for longer system life.
- Rolls reverse for cutting in both directions to increase productivity.
- Larger than industry normal precision ground pressure rollers for minimal deflection during cutting.
- Industry leading design, construction, features and customer support.

DESCRIPTION:

Starview's RP Series Roller Die Cutters are versatile enough to handle a full range of low to high production requirements. These machines will trim a wide range of materials such as skin packaged products, thermoformed products, cork, rubber and any other application where a steel rule die can be utilized.

Single driven pressure roller machines **RP-1 Series** may be used where cutting registration is not critical and cutting pressures are low. Double driven **RP-2 Series** pressure roller machines should be used where registration is important or for higher cutting pressures.

For applications where it is advantageous to cut with the product facing up or to have the ability to program cutting without manufacturing steel rule dies for each configuration please consider or **SDC Series** Slitter/Die Cutters.



SPECIFICATIONS:

	RP22-1	RP28-2	RP34-2
Maximum die width:	23.0"	29.0"	35.0"
Maximum die length:	Unlimited with support	Unlimited with support	Unlimited with support
Max die height std:	6.0"	6.0"	6.0"
Driven rolls:	Lower	Upper & Lower	Upper & Lower
Diameter-pressure rolls:	5.5"	7.5"	7.5"
Motor horsepower:	1	2	2
Average cycle speed:	1 – 4 cpm	1 – 4 cpm	1 – 4 cpm
Electrical:	208-240 Volts / 3 PH / 8 Amps	208-240 Volts / 3 PH / 15 Amps	208-240 Volts / 3 PH / 15 Amps

	RP40-2	RP54-2
Maximum die width:	41.0"	55.0"
Maximum die length:	Unlimited with support	Unlimited with support
Max die height std:	6.0"	6.0"
Driven rolls:	Upper & Lower	Upper & Lower
Diameter-pressure rolls:	7.5"	7.5"
Motor horsepower:	2	3
Average cycle speed:	1 – 4 cpm	1 – 4 cpm
Electrical:	208-240 Volts / 3 PH / 15 Amps	208-240 Volts / 3 PH / 20 Amps

Specifications and model availability are subject to change without notice.

Please request specific model quotations for complete pricing, specifications and options from your local distributor. Feel free to contact Starview to obtain the contact information for the authorized distributor in your area.



view a video about these products on



Starview Packaging Machinery, Inc.

Leading the industry

With innovative packaging machine designs for:

**Blister & Clamshell Sealing · Medical / Pharmaceutical Packaging · Stretch Pak Packaging
Skin Packaging and Die Cutting · Food Tray Packaging · Thermoforming / Vacuum Forming
Customized Packaging Equipment · Systems with Automation & Integration**

1840 St. Regis Blvd.
Dorval, Quebec H9P 1H6
Tel: 514-920-0100
Fax: 514-920-0092
Toll Free: 888-278-5555
www.starview.net
sales@starview.net