



Sytec 701

Cross-Linked Shrink Film

GENERAL PURPOSE, VERY FORGIVING FILM WITH WIDE SEAL & SHRINK TEMPERATURE RANGE

Options: Pre-Perforation, Printed • Gauges: 45, 60, 75, & 100



Sytec 701D

Cross-Linked Shrink Film Designed for Heavy Duty Packaging

REPLACES TRADITIONAL CORRUGATED BOX OR HEAVY GAUGE POLYETHYLENE

Options: Pre-Perforation, Printed • Gauges: 125, 150, 200 & 300



Sytec MVP

Soft Durable Low Shrink Force Cross-Linked Shrink Film

IDEAL FOR SOFT ITEMS & ODD SHAPED PRODUCTS

Options: Pre-Perforation, Printed • Gauges: 45, 60, 75 & 100



Sytec 307S

Very Strong, Hi-Slip, Shrink Film

ESPECIALLY SUITABLE FOR HI-SPEED AUTOMATIC APPLICATIONS

Options: Pre-Perforation, Printed • Gauges: 50, 60, 75 & 100



Symax Film

Ultra-Thin Cross-Linked Shrink Film

GREAT SOLUTION FOR LIGHTWEIGHT PRODUCTS ALLOWING FOR A LOWER GAUGE FILM AND PROVIDING MORE FOOTAGE PER ROLL.

Options: Pre-Perforation • Gauges: 35



Syfresh AF

Anti Fog Shrink Film to Enhance Presentation and Extend Freshness of Fresh Foods and Produce

THE SPECIAL PROPERTIES OF THIS FILM ALLOW FOR EXCEPTIONAL PERFORMANCE ON HIGH SPEED FLOW PACK EQUIPMENT.

Options: Pre-Perforation, Printed • Gauges: 45, 60 & 75

ENHANCED PERFORMANCE SHRINK FILMS

SYFAN FILM FEATURES

- Product protection • User-friendly • Excellent optical properties

SHRINK & SEAL PROPERTIES

- Quick shrinkage • Outstanding stability • Strong seals

See individual data sheets for complete descriptions and properties.

SYFAN FILM FEATURES

Gauge	35	45	50	60	75	100	125	150	200	300
C/F	7,500'	5,830'	5,250'	4,375'	3,500'	2,625'	2,100'	1,750'	1,310'	875'
SW	15,000'	11,660'	10,500'	8,750'	7,000'	5,250'	4,200'	3,500'	2,620'	1,750'

Standard Widths are from 6" to 32" in 2" increments. Net Roll Weight is approximately 2.1lb x width (inches)/Gross Roll Weight is approximately 2.3 lb x width (inches). Call for special sizes, gauges & roll configurations.

DELIVERIES

- Standard inventory items are available for pick up or ship within 24 hours
- Out of stock STANDARD items will be replenished within 5-10 business days
- Single wound film delivery within 5-10 business days

FOOD CONTACT: All Syfan Polyolefin Shrink films are approved for direct food contact. All Syfan films comply with the requirements & regulations which state that materials may be safely used in food contact and non-food applications. These specifications are described in the FDA code Title 21 para. 177.1520 and in the EC Commission Directive No. 90/128/EEC.

SAFETY & ENVIRONMENT: SYFAN SHRINK FILMS contain no CFC's nor any residues of the heavy metals Sb, Cr, As, Pb, Ba, Cd, Ag, Se. The gas generated during sealing of SYFAN SHRINK FILM is comprised of hydrocarbon derivatives of the pure raw material and contains no harmful substances, irritants, or chlorine derivatives.

distributed by



Syfan USA
 1622 Twin Bridges Rd., P.O. Box 203, Everetts, NC 27825
Main: 252.792.2547 Fax: 252.792.3185
 syfanusa.com