ALPHA

AUTOMATIC L-SEALER

SHRINK TECH SYSTEMS



Features:

- PLC Controlled with Full Touch Screen & 15 Individual Set-Ups
- Vertical Stroke, Solid Seal Blade System With Center Line Sealing
- Adjustable Pin Perf for Air Evacuation
- On Board Fault Detection & Troubleshooting
- Soft Start & Soft Stop Conveyors
- Multi-Pack Feature
- Horizontal & Vertical Eyes Standard
- Cogged Film Puller Belts
- Quick Change Over with Easy Adjustments
- Variable Speed Scrap Wind-up System
- Available with Closing Conveyor & System Variable Speed
- Available with Print Registration
- Guarding with Safety Switches
- Strong, Durable Construction

Specifications:

Machine Size:	70” L x 42” W x 60” H		
Seal Bar Size:	28” L x 24” W		
Package Size:		Min.	Max.
	L	4”	26”
	W	2”	22”
	H	.125”	8”
Max. Film Width:	29” Centerfolder Film		
Conveyor Speed:	80FPM		
Product Speed:	35 + PPM (Product Pending)		
Power Requirements:	120v / 1PH / 20 AMPS		
Air Requirements:	90 PSI 5CFM		

Made In The USA
Shrink Tech Systems
Saint Louis, Missouri

MEMBER PMMI

1226 AMBASSADOR BLVD. ST. LOUIS MISSOURI 63132

PHONE: 314.997.4259 www.shrinktechsystems.com FAX: 314.995.7006